

# Generator set data sheet



**Model:** DQPAA  
**Frequency:** 60 Hz  
**Fuel type:** Diesel  
**kW rating:** 600 Standby  
**Emissions level:** EPA NSPS Stationary Emergency Tier 2

Exhaust emission data sheet:	EDS-1154
Exhaust emission compliance sheet:	EPA-1224
Sound performance data sheet:	MSP-1152
Cooling performance data sheet:	MCP-240
Prototype test summary data sheet:	PTS-316
Standard set-mounted radiator cooling outline:	A041U110
Optional set-mounted radiator cooling outline:	
Optional heat exchanger cooling outline:	
Optional remote radiator cooling outline:	

Fuel consumption	Standby				Prime				Continuous			
	kW (kVA)				kW (kVA)				kW (kVA)			
Ratings	600 (750)				545 (681)							
Load	1/4	1/2	3/4	Full	1/4	1/2	3/4	Full	1/4	1/2	3/4	Full
US gph	13.0	23	33.5	45.4	12.2	21.2	29.8	41.0				
L/hr	49.2	87	123	171.8	46.2	80.3	112.8	155.2				

Engine	Standby rating	Prime rating	Continuous rating
Engine manufacturer	Cummins Inc.		
Engine model	QSK19-G8		
Configuration	Cast Iron, in line 6 cylinder		
Aspiration	Turbocharged and charged after-cooled (air- to-air)		
Gross engine power output, kWm (bhp)	721 (967)	608 (815)	
BMEP at set rated load, kPa (psi)	2552 (370)	2151 (312)	
Bore, mm (in)	158.8 (6.25)		
Stroke, mm (in)	158.8 (6.25)		
Rated speed, rpm	1800		
Piston speed, m/s (ft/min)	9.5 (1875)		
Compression ratio	15:1		
Lube oil capacity, L (qt)	68.1 (72)		
Overspeed limit, rpm	2070		
Regenerative power, kW	59		

Fuel flow	
Maximum fuel flow, L/hr (US gph)	492 (130)
Maximum fuel inlet restriction, kPa (in Hg)	30.5 (9)
Maximum fuel inlet temperature, °C (°F)	71 (160)
Maximum fuel return line restriction kPa (in Hg)	33.8 (10)

<b>Air</b>	<b>Standby rating</b>	<b>Prime rating</b>	<b>Continuous rating</b>
Combustion air, m <sup>3</sup> /min (scfm)	59.8 (2112)	56.3 (1689)	
Maximum air cleaner restriction, kPa (in H <sub>2</sub> O)	6.2 (25)		
Alternator cooling air, m <sup>3</sup> /min (cfm)	117 (4156)		

### **Exhaust**

Exhaust flow at set rated load, m <sup>3</sup> /min (cfm)	150 (5319)	138 (4901)	
Exhaust temperature, °C (°F)	508 (946)	486 (906)	
Maximum back pressure, kPa (in H <sub>2</sub> O)	3.4 (13.6)		

### **Standard set-mounted radiator cooling**

Ambient design, °C (°F)	52 (126)	50 (122)	
Fan load, kW <sub>m</sub> (HP)	26.1 (35)		
Coolant capacity (with radiator), L (US gal)	95 (25.3)		
Cooling system air flow, m <sup>3</sup> /min (scfm)	1007 (35588)		
Total heat rejection, MJ/min (Btu/min)	29.8 (28291)	24.4 (23118)	
Maximum cooling air flow static restriction, kPa (in H <sub>2</sub> O)	0.12 (0.5)		

### **Optional set-mounted radiator cooling**

Ambient design, °C (°F)			
Fan load, kW <sub>m</sub> (HP)			
Coolant capacity (with radiator), L (US gal)			
Cooling system air flow, m <sup>3</sup> /min (scfm)			
Total heat rejection, MJ/min (Btu/min)			
Maximum cooling air flow static restriction, kPa (in H <sub>2</sub> O)			
Maximum fuel return line restriction, kPa (in Hg)			

<b>Optional heat exchanger cooling</b>	<b>Standby rating</b>	<b>Prime rating</b>	<b>Continuous rating</b>
Set coolant capacity, L (US gal)			
Heat rejected, jacket water circuit, MJ/min (Btu/min)			
Heat rejected, aftercooler circuit, MJ/min (Btu/min)			
Heat rejected, fuel circuit, MJ/min (Btu/min)			
Total heat radiated to room, MJ/min (Btu/min)			
Maximum raw water pressure, jacket water circuit, kPa (psi)			
Maximum raw water pressure, aftercooler circuit, kPa (psi)			
Maximum raw water pressure, fuel circuit, kPa (psi)			
Maximum raw water flow, jacket water circuit, L/min (US gal/min)			
Maximum raw water flow, aftercooler circuit, L/min (US gal/min)			
Maximum raw water flow, fuel circuit, L/min (US gal/min)			
Minimum raw water flow at 27 °C (80 °F) inlet temp, jacket water circuit, L/min (US gal/min)			
Minimum raw water flow at 27 °C (80 °F) inlet temp, aftercooler circuit, L/min (US gal/min)			
Minimum raw water flow at 27 °C (80 °F) inlet temp, fuel circuit, L/min (US gal/min)			
Raw water delta P at min flow, jacket water circuit, kPa (psi)			
Raw water delta P at min flow, aftercooler circuit, kPa (psi)			
Raw water delta P at min flow, fuel circuit, kPa (psi)			
Maximum jacket water outlet temp, °C (°F)			
Maximum aftercooler inlet temp, °C (°F)			
Maximum aftercooler inlet temp at 25 °C (77 °F) ambient, °C (°F)			
Maximum fuel return line restriction, kPa (in Hg)			

### **Optional remote radiator cooling<sup>1</sup>**

Set coolant capacity, L (US gal)			
Max flow rate at max friction head, jacket water circuit, L/min (US gal/min)			
Max flow rate at max friction head, aftercooler circuit, L/min (US gal/min)			
Heat rejected, jacket water circuit, MJ/min (Btu/min)			
Heat rejected, aftercooler circuit, MJ/min (Btu/min)			
Heat rejected, fuel circuit, MJ/min (Btu/min)			
Total heat radiated to room, MJ/min (Btu/min)			
Maximum friction head, jacket water circuit, kPa (psi)			
Maximum friction head, aftercooler circuit, kPa (psi)			
Maximum static head, jacket water circuit, m (ft)			
Maximum static head, aftercooler circuit, m (ft)			
Maximum jacket water outlet temp, °C (°F)			
Maximum aftercooler inlet temp at 25 °C (77 °F) ambient, °C (°F)			
Maximum aftercooler inlet temp, °C (°F)			
Maximum fuel flow, L/hr (US gph)			
Maximum fuel return line restriction, kPa (in Hg)			

## Weights<sup>2</sup>

Unit dry weight kgs (lbs)	5211 (11488)
Unit wet weight kgs (lbs)	5352 (11799)

### Notes:

<sup>1</sup> For non-standard remote installations contact your local Cummins representative.

<sup>2</sup> Weights represent a set with standard features. See outline drawing for weights of other configurations.

## Derating factors

<b>Standby</b>	Engine power available up to 1860 m (6102 ft) at ambient temperatures up to 40 °C (104 °F). Above these elevations, derate at 1.7% per 300 m (1000 ft). Above 40 °C (104 °F) derate 6.7% per 10 °C (18 °F).
<b>Prime</b>	Engine power available up to 2174 m (7133 ft) at ambient temperatures up to 40 °C (104 °F). Above these elevations, derate at 3% per 300 m (1000 ft). Above 40 °C (104 °F) derate 9% per 10 °C (18 °F).
<b>Continuous</b>	

## Ratings definitions

<b>Emergency Standby Power (ESP):</b>	<b>Limited-Time Running Power (LTP):</b>	<b>Prime Power (PRP):</b>	<b>Base Load (Continuous) Power (COP):</b>
Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. Emergency Standby Power (ESP) is in accordance with ISO 8528. Fuel Stop power in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power to a constant electrical load for limited hours. Limited-Time Running Power (LTP) is in accordance with ISO 8528.	Applicable for supplying power to varying electrical load for unlimited hours. Prime Power (PRP) is in accordance with ISO 8528. Ten percent overload capability is available in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power continuously to a constant electrical load for unlimited hours. Continuous Power (COP) is in accordance with ISO 8528, ISO 3046, AS 2789, DIN 6271 and BS 5514.

## Alternator data

Voltage	Connection <sup>1</sup>	Temp rise °C	Duty <sup>2</sup>	Single phase factor <sup>3</sup>	Max surge kVA <sup>4</sup>	Winding No.	Alternator	Feature code
600	Wye	80	S/P		2944	7	ADS-309	B305-2
600	Wye	105	S/P		2429	17	ADS-308	B304-2
240/480	Wye	80	S/P		2944	311	ADS-309	B969-2
240/480	Wye	105	S/P		2429	311	ADS-308	B970-2
190/380-208/416	Wye	105	S/P		2429	14	ADS-308	B972-2
220/440-240-480	Wye	105	S		2944	311	ADS-309	B973-2
208/416-240/480	Wye	125	S		2944	311	ADS-309	B975-2
380	Wye	80	P		2944	13	ADS-309	B687-2
220/440-240/480	Wye	80	P		2944	311	ADS-309	B973-2
208/416-240/480	Wye	80	P		2944	311	ADS-309	B975-2

### Notes:

<sup>1</sup> Limited single phase capability is available from some three phase rated configurations. To obtain single phase rating, multiply the three phase kW rating by the Single Phase Factor<sup>3</sup>. All single phase ratings are at unity power factor.

<sup>2</sup> Standby (S), Prime (P) and Continuous ratings (C).

<sup>3</sup> Factor for the *Single Phase Output from Three Phase Alternator* formula listed below.

<sup>4</sup> Maximum rated starting kVA that results in a minimum of 90% of rated sustained voltage during starting.

## Formulas for calculating full load currents:

### Three phase output

$$\frac{\text{kW} \times 1000}{\text{Voltage} \times 1.73 \times 0.8}$$

### Single phase output

$$\frac{\text{kW} \times \text{Single Phase Factor} \times 1000}{\text{Voltage}}$$

**Warning:** Back feed to a utility system can cause electrocution and/or property damage. Do not connect to any building's electrical system except through an approved device or after building main switch is open.

For more information contact your local Cummins distributor  
or visit [power.cummins.com](http://power.cummins.com)

Our energy working for you.™

